

Box: Patent Application  
THE HONORABLE COMMISSIONER OF PATENTS AND TRADEMARKS  
Washington, D.C. 20231-9998

Sir:

Transmitted herewith for filing is the patent application of: Richard Joseph Oliver and Roger Mather Duvall

Title: A METHOD AND SYSTEM FOR PROVIDING ENHANCED EDITING CAPABILITIES

Enclosed are:

- (X) Three (3) sheets of Formal Drawings including four (4) figures.
- (X) An Assignment of the invention to: Sony Corporation.
- (X) A Declaration and Power of Attorney.
- ( ) A Verified Statement to establish Small Entity Status under 37 CFR 1.9 and 37 CFR 1.27.

The Filing Fee has been calculated as shown below:

For:	(Col. 1)	(Col. 2)	SMALL ENTITY		OTHER THAN A SMALL ENTITY	
	No. Filed	No. Extra	RATE	FEE	RATE	FEE
Basic Fee:	-	-	-	\$385.00	-	\$770.00
Total Claims:	16-20	= 0	x \$11.00		x \$22.00	0
Indep. Claims:	2-3	= 0	x \$40.00		x \$80.00	0
<input type="checkbox"/> Multiple Dep. Claim(s) Presented			+ \$130.00		+ \$260.00	0
* If the difference in (Col. 1) is less than zero, enter "0" in (Col. 2)			Total:	\$	Total:	\$770.00

- (X) A check in the amount of \$770.00 to cover the filing fee is enclosed.
- (X) A check for \$40.00 covering Recordation of the Assignment is enclosed, along with the Assignment Cover Sheet.
- (X) The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to our Deposit Account No. 02-2666. A duplicate copy of this sheet is enclosed.
- (X) Any additional filing fees required under 37 CFR 1.16.
- (X) Any patent application processing fees under 37 CFR 1.16.
- (X) The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to our Deposit Account No. 02-2666. A duplicate copy of this sheet is enclosed.
- (X) Any extension or petition fees under 37 CFR 1.17.
- (X) Any filing fees under 37 CFR 1.16 for presentation of extra claims.

Respectfully submitted,

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP

Date: 9/24/97

Thomas Coester  
Thomas M. Coester, Reg. No. 39,637

12400 Wilshire Boulevard, Seventh Floor  
Los Angeles, California 90025-1026  
(310) 207-3800

**UNITED STATES PATENT APPLICATION**

**FOR**

**A METHOD AND SYSTEM FOR PROVIDING  
ENHANCED EDITING CAPABILITIES**

Inventors:  
Richard Joseph Oliver  
Roger Mather Duvall

Prepared By:

**BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN**  
12400 Wilshire Boulevard, Seventh Floor  
Los Angeles, California 90025-1026  
(310) 207-3800

Express Mail No. EH833458144US

## **BACKGROUND OF INVENTION**

### **1. Field of the Invention**

5           The invention relates to digital signal processing. More specifically, the invention relates to a recording technique applicable to a media stream, which provides enhanced editing features.

### **2. Related Art**

10

Recording of a media stream, for example an audio stream, has in the past typically been recorded on a continuous tape. At the time recording was to begin, a user would punch in and the tape would begin to record continuously until the user punched out. The subsequent punch in would take up from the point of the previous punch out. Ultimately, for editing purposes it might be desirable to

15           rewind the tape and record over some portion of it. The result achieved might be for example, a segment of the original recording followed by a segment that was recorded over followed by more of the original recording. In this technique the original recording in the rerecorded segment is lost and cannot be recovered.

20

Accordingly, this type of editing is known as destructive editing.

More recently, the use of computers and more particularly random access storage media in sound recording has significantly changed the format and editing possibilities available. Two such possibilities are non-linear editing and non-

25           destructive editing. Non-linear editing amounts to the manipulation of pointers to media files. Non-destructive editing requires that all original media files be maintained. This permits edits to be undone, including a record over edit, simply by pointer manipulation. The down side to non-destructive editing is that it uses

more disk space than is represented to the user. In spite of this down side, non-destructive editing has gained wide acceptance.

**Figure 1** is a diagram of an example of a prior art non-linear non-destructive editing technique. The user view of a media track is an event list. An event is a software object including a media file ID, an off-set into the media file, and a length from the offset. For example, a first media file 1 might be given ID 1. The event may then have an offset of zero, meaning it starts at the first sample of the media file 1, and a length of ten, meaning that the first ten samples beginning at the offset (here zero) will appear in the user view of the recording. Thus, referring to figure 1, the first media file 1 with ID 1 and a second media file 2 with ID 2 are saved to a random access medium. A users view 10 of the track is an event list having three events of the form ID, offset, length: 1, 0, 10; 2, 0, 10 and 1, 20, 10. This assumes a length of ten samples which is artificially short for most real world applications, but nevertheless, suitable for illustration. Thus, while the random access device such as a hard disk contains media file 1 in its entirety and media file 2 in its entirety, from the user perspective the track contains the first ten samples of media file 1, followed by rerecorded region 8 containing ten samples of media file 2, which is in turn followed by the last ten samples from media file 1. The dotted lines in media file 1 delimit the rerecorded region 8 from the users perspective.

Notably, the beginning of media file 1 coincides exactly with the punch in point 5 and the end of media file 1 coincides exactly with the punch out point 6. An analogous case exists with respect to media file 2. The punch in point 5 and the punch out point 6 are the points at which the recording device receives the signal to begin recording or end recording respectively. Thus, particularly in the editing context where one is trying to record over a region of an existing track, a high degree

of precision is required to properly time the begin and end of the rerecorded region 8 to achieve the desired effect. Even using nonlinear and nondestructive editing techniques if the punch in is too late or the punch out is too early, media file 2 will need to be discarded and another attempt to record the desired segment will be  
5 required.

In view of the foregoing, it would be desirable to be able to accommodate the imprecision of users punching in and punching out, thereby providing enhanced editing possibilities and improved editing efficiency.

10

## **BRIEF DESCRIPTION OF THE DRAWINGS**

**Figure 1** is a diagram of an example of a prior art non-linear non-destructive editing technique.

5

**Figure 2** is a block diagram of a system of one embodiment of the invention.

**Figure 3** is a flow chart of buffer operation in one embodiment of the invention after steady state is reached.

10

**Figure 4** is a diagram of editing using a media file with the record handles of one embodiment of the invention.

## SUMMARY OF THE INVENTION

A method and system for providing enhanced editing capability is disclosed.

As with analog audio technology such as tape machines, most digital media

- 5 recorders save data from the media input only when explicitly placed in record mode. Normally the desire is that a specific interval of media input be saved to permanent storage. However, if the system is placed in record mode any later than the start of the interval, or taken out of record mode any earlier than the end of the interval, input data near the ends of the interval will be lost. This invention
- 10 guarantees that media data stays in a buffer for at least a minimum amount of time after it has been received at the input, regardless of whether the system is in record mode or not. When the user enters record mode (punches in) the incoming media input data is designated to be permanently stored on, for example, a hard disk. Additionally, buffered data for the media just prior to the punch in point is also
- 15 designated to be stored to permanent storage. When the user leaves record mode (punches out) data for a predetermined period of time after punch out is also designated to be permanently stored. The extra media data before the punch in point and after the punch out point are referred to as record handles. From the users view, the audio track does not include the record handles, but the data in the
- 20 record handles can be accessed by manipulating pointers in the event list to include some, all or none of the record handles (at which point the user view will include the selected portion of the record handle(s)). In this manner, the difficulty of precisely timing the punch in and punch out points is alleviated.

## DETAILED DESCRIPTION OF THE INVENTION

Figure 2 is a block diagram of a system of one embodiment of the invention.

One or more media input streams 11 are provided to a digital signal processor (DSP)

5 13. A one to one correspondence between input streams and DSP's 13 is not required. The DSP 13 continually sources the incoming media to buffer 14. Buffer 14 has portions thereof allocated to accommodate each of the incoming media streams 11. Buffer 14 is also coupled to a bus 19. A host processor 15 is directly coupled to a memory 16 and also coupled to the bus 19. A Small Computer System  
10 Interface (SCSI) controller 17 is coupled to bus 19 and to a mass storage device 20 via a SCSI bus 18. DSP's 13 are also coupled to bus 19.

In one embodiment, bus 19 is a Peripheral Component Interconnect (PCI) bus.

The mass storage device is a removable rotating magnetic disc having a SCSI port.

15 This allows the mass storage device to be readily disconnected and exchanged for a new device thereby limiting the effect of disk space constraints. The buffer 14 is comprised of 32 megabytes of random access memory (RAM). In such system if 16 media input streams and 16 media output streams exist, nominally one megabyte of the buffer will be allocated to each input stream. If the media input stream is a 16-bit  
20 audio stream, one megabyte corresponds to approximately ten seconds of audio data. Typical audio data is either 16-bit or 24-bit audio at 48 kHz. The allocated portion of buffer 14 is further broken down into a number of blocks. A block is equal to a transaction size between the buffer 14 and mass storage 20 device. Because of the overhead of conducting each transaction, it is desirable to make the block size  
25 relatively large. In one embodiment, a 64 kB block size is used. For 16-bit audio at 48kHz, this means each block contains approximately two thirds of a second of audio data. Once the allocated portion of the buffer 14 is full, a steady state condition exists



wherein as each block is filled an oldest block of data in the allocated portion of buffer 14 must be reallocated to be overwritten.

The DSP 13 receiving the media input stream 11 adjusts the input gain,  
5 detects for overflow errors and packs the media data for storage in the buffer 14. In the embodiment discussed above, because while the device is on the buffer is continually receiving new data from the input channel, after approximately ten seconds the portion of buffer 14 allocated to a particular channel will be full and will remain full (e.g., in steady state) throughout the remainder of the recording session.

10 Host processor 15 is responsible for allocation of blocks in the buffer as well as designating blocks in the buffer to be permanently stored. Subsequent to receipt of a punch in signal, blocks of data in the buffer corresponding to a previous user settable interval (e.g., one second by default) of time are tagged for subsequent  
15 permanent storage to the mass storage device. The punch in signal may be received from the user interface, over a network, or via a DSP generated interrupt. Additionally, all blocks between the punch in signal and a next punch out signal will be tagged for permanent storage. Once the punch out signal is received blocks corresponding to a user settable period of time (e.g., one second by default) following  
20 the punch out signal will also be tagged for permanent storage. In this way blocks of data before the punch in signal and data after the punch out signal will be saved to mass storage device 20 when the blocks are checked for reallocation. Thus, mass storage device 20 will contain a media file having a first record handle, an intended record interval, and a second record handle. Notably, the size of the blocks will  
25 likely cause more than the user set amount of data to be permanently stored. However, if the user has designated one second record handle, the system guarantees the extra data saved will be at least one second worth of data.

Typically each record interval is saved to its own media file. However, in some cases a user may punch in, punch out and punch back in again. If the record handles for the record intervals overlap, both intervals will be saved to a common media file and will share a common record handle between them. From the user  
5 view, the common media file appears as two events, one corresponding to each record interval.

**Figure 3** is a flow chart of buffer operation in one embodiment of the invention after steady state is reached. Throughout a recording session media data  
10 is continually flowing into and being saved in the buffer. The system watches for a punch in signal indicating that a record interval is commencing. As used herein a recording session is a period of time that may contain one or more record intervals. A record interval is the period between a punch in and a corresponding punch out. A determination is made, at decision block 101, if a punch in signal has been  
15 received. If it has, at functional block 102, the block(s) of the buffer containing the previous one second of samples from the input stream are tagged for storage. At functional block 103, the current block is tagged for storage. A determination is made, at decision block 104, if the block should be allocated.

20 If a block needs to be reallocated, then at decision block 105, a determination is made if the oldest block of data has been tagged for storage. If it has, at functional block 106, the block is stored to the mass storage device. Otherwise or after storage occurs, the oldest block is reallocated to be overwritten at functional block 107. A determination is then made at decision block 108 if a record interval is in progress.  
25 A record interval is deemed to be in progress if a punch in signal has been received and no corresponding punch out signal has been received. If a record interval is in progress, the reallocated block is tagged for storage at functional block 109. If the block is not full, at decision block 104, or after tagging the block for storage at

functional block 109, a determination is made if a punch out signal has been received at decision block 110. If no punch out signal has been received the system returns to decision block 104. Otherwise, once the punch out signal is received, at functional block 111 the blocks containing the following one second of input data are tagged for storage.

Figure 4 is a diagram of editing using a media file with the record handles of one embodiment of the invention. The user view event list 200 is composed of three events 211, 212, and 213. Events 211 and 213 are from media file 1. Event 212 corresponds with rerecorded segment in 208 of media file 1. Event 212 is provided from media file 3 which has been recorded in accordance with one embodiment of the invention. In this example, record handles 214 and 215 are three samples long. Nominal punch in point 202 and the nominal punch out point 203 are the default boundaries of what the user sees in the event list for the track. However, because the record handles the effective punch in point and punch out point can be moved up to three samples earlier for the punch in point or three samples later for the punch out point. Thus, while the default user event list would be for example 1, 0, 10; 3, 3, 10; 1, 20, 10 (following the format media file ID, offset, length) the user could shift the end points 206 and 207 of event 212 to be 205 and 210 with a resulting event list being 1, 0, 8; 3, 1, 14; and 1, 22, 8. Other shifts are of course possible. This shifts the effective punch in point of media file 3 to point 204. While there need be no explicit shift of nominal punch out point 203, in the above example if no record handle 215 existed, an error would be generated.

Numerous other editing possibilities exist given the existence of the record handles. For example, if the media file record interval of media file 3 is out of sync with other tracks (not shown), a user can simply slide the effective punch in point to an earlier sample and maintain the same length thereby resyncing the tracks. Also

as noted above, because the typical block size does not provide perfect granularity, there may be more extra input data actually stored to the media file than the, e.g. one second record handle. In such case, the system may either permit the user to access all stored data or restrict the user to the explicitly set record handle size.

5 While the invention is particularly useful in an audio context, it would also be suitable for use with other continuous stream media such as, without limitation, video and Musical Instrument Digital Interface (MIDI) data. All of these options are within the scope and contemplation of the invention.

10 In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes can be made thereto without departing from the broader spirit and scope of the invention as set forth in the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather  
15 than a restrictive sense. Therefore, the scope of the invention should be limited only by the appended claims.

## CLAIMS

What is claimed is:

- 1 1. A method comprising the step of:  
2 receiving a media input stream;  
3 saving data corresponding to the media input stream in a buffer continuously  
4 during a time interval; and  
5 selecting portions of the buffer for storage in a media file on a mass storage  
6 device responsive to a punch in signal and a punch out signal wherein the media  
7 file contains input stream data for a time window greater than a time window  
8 between the punch in signal and the punch out signal.
- 1 2. The method of claim 1 wherein the media file comprises:  
2 a first record handle before a punch in point;  
3 a second record handle between a punch out point and the end of the media  
4 file; and  
5 a record interval between the punch in point and the punch out point.
- 1 3. The method of claim 1 wherein the media input stream is an audio stream  
2 and the time interval is a recording session.
- 1 4. The method of claim 3 further comprises the steps of :  
2 editing an event list for an audio track by inserting an event corresponding to  
3 the media file; and  
4 adjusting an offset and a length of the event to include a portion of at least  
5 one record handle.
- 1 5. The method of claim 4 wherein in the first record handle is approximately  
2 one second of audio data preceding the punch in signal and the second record  
3 handle is approximately one second of audio data following the punch out signal.

1 6. The method of claim 1 further comprising the step of allocating a portion of  
2 the buffer to each of a plurality of input channels wherein a plurality of media input  
3 streams source data to the plurality of input channels.

1 7. A method of claim 1 wherein the step of selecting comprises the steps of:  
2 tagging a buffer block filled preceding the punch in signal with a storage tag;  
3 tagging all buffer blocks between the punch in signal and punch out signal  
4 with a storage tag; and  
5 tagging a buffer block filled following the punch out signal with a storage tag.

1 8. The method of claim 7 further comprising the steps of:  
2 checking a buffer block for a storage tag prior to reallocating the buffer block to  
3 be overwritten;  
4 storing all contiguous buffer blocks containing a storage tag in the mass  
5 storage device as the media file; and  
6 reallocating the buffer block to be overwritten if no storage tag exist or after  
7 the data has been stored to the media file if a storage tag exists.

1 9. A system comprising:  
2 a signal processor for processing a media input stream;  
3 a buffer coupled to the signal processor, the buffer for continuously loading  
4 data corresponding to the media input stream while the media input stream exists;  
5 and  
6 a mass storage device coupled to the buffer by a bus, the mass storage device  
7 for storing a media file derived from the media input stream comprising media  
8 samples preceding a punch in signal, media samples following a punch out signal,  
9 and a plurality of media samples between the punch in signal and the punch out  
10 signal.

1 10. The system of claim 9 further comprises a host processor for controlling the  
2 storage of data from the buffer to the mass storage device.

1 11. The system of claim 9 wherein the buffer is both loaded and unloaded in a  
2 first in first out (FIFO) manner such that once the buffer is full an oldest block of  
3 data in the buffer will be reallocated to be overwritten on a next load.

1 12. The system of claim 11 wherein responsive to a punch in signal a data block  
2 earlier in time than the punch in signal is tagged for storage to the mass storage  
3 device.

1 13. The system of claim 11 wherein if the oldest block of data is tagged for storage  
2 the oldest block will be stored to the mass storage device before being reallocated.

1 14. The system of claim 13 wherein any block containing data from one second  
2 before punch in until one second after punch out is tagged for storage in a single  
3 media file on the mass storage device.

1 15. The system of claim 9 wherein the buffer is a random access memory (RAM).

1 16. The system of claim 15 wherein the input stream comprises up to sixteen  
2 channels and the RAM is logically allocated amongst the channels.

## **ABSTRACT OF THE DISCLOSURE**

A method and system for providing enhanced editing capability of media data. Media data arriving in a continuous stream is saved in a buffer. When a user enters record mode, some data received before record mode was entered is designated for permanent storage. Similarly, all data received while in record mode is designated for permanent storage. Once the user leaves record mode, additional data received after leaving record mode is also designated for permanent storage. In due course all data designated for permanent storage is stored to a mass storage device. Any data in the buffer not designated for permanent storage will be overwritten without being stored to the mass storage device. In this manner, a media file having record handles is created. The record handles permit a user to slide the nominal entry and exit from record mode to accommodate timing and synchronization errors.



**DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below, next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

**A METHOD AND SYSTEM FOR PROVIDING ENHANCED EDITING CAPABILITIES**

the specification of which

XXX is attached hereto.  
 \_\_\_\_\_ was filed on \_\_\_\_\_ as  
 Application Serial No. \_\_\_\_\_  
 and was amended on \_\_\_\_\_  
 (if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I do not know and do not believe that the same was ever known or used in the United States of America before my invention thereof, or patented or described in any printed publication in any country before my invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months prior to this application.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119, of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

<u>Prior Foreign Application(s)</u>			<u>Priority Claimed</u>	
<u>(Number)</u>	<u>(Country)</u>	<u>(Day/Month/Year Filed)</u>	<u>Yes</u>	<u>No</u>
_____	_____	_____	_____	_____
<u>(Number)</u>	<u>(Country)</u>	<u>(Day/Month/Year Filed)</u>	<u>Yes</u>	<u>No</u>
_____	_____	_____	_____	_____

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing Date)	(Status -- patented, pending, abandoned)
(Application Serial No.)	(Filing Date)	(Status -- patented, pending, abandoned)
(Application Serial No.)	(Filing Date)	(Status -- patented, pending, abandoned)

I hereby appoint BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN, a firm including: Aloysius T. C. AuYeung, Reg. No. 35,432; William Thomas Babbitt, Reg. No. 39,591; Jordan Michael Becker, Reg. No. 39,602; Bradley J. Berezna, Reg. No. 33,474; Michael A. Bernadieu, Reg. No. 35,934; Roger W. Blakely, Jr., Reg. No. 25,831; Gregory D. Caldwell, Reg. No. 39,926; Kent M. Chen, Reg. No. 39,630; Lawrence M. Cho, Reg. No. 39,942; Thomas M. Coester, Reg. No. 39,637; Roland B. Cortes, Reg. No. 39,152; William Donald Davis, Reg. No. 38,428; Michael Anthony DeSanctis, Reg. No. 39,957; Daniel M. De Vos, Reg. No. 37,813; Tarek N. Fahmi, Reg. No. P41,402; James Y. Go, Sharmini Nathan Green, Reg. No. 41,410; Reg. No. 40,621; David R. Halvorson, Reg. No. 33,395; Eric Ho, Reg. No. 39,711; George W. Hoover II, Reg. No. 32,992; Eric S. Hyman, Reg. No. 30,139; Dag H. Johansen, Reg. No. 36,172; Stephen L. King, Reg. No. 19,180; Michael J. Mallie, Reg. No. 36,591; Kimberley G. Nobles, Reg. No. 38,255; Ronald W. Reagan, Reg. No. 20,340; James H. Salter, Reg. No. 35,668; William W. Schaal, Reg. No. 39,018; James C. Scheller, Reg. No. 31,195; Charles E. Shemwell, Reg. No. 40,171; Maria McCormack Sobrino, Reg. No. 31,639; Stanley W. Sokoloff, Reg. No. 25,128; Allan T. Sponseller, Reg. No. 38,318; Steven R. Sponseller, Reg. No. 39,384; Edwin H. Taylor, Reg. No. 25,129; George G. C. Tseng, Reg. No. 41,355; Lester J. Vincent, Reg. No. 31,460; John Patrick Ward, Reg. No. 40,216; Ben J. Yorks, Reg. No. 33,609; and Norman Zafman, Reg. No. 26,250; my attorneys; and Robert Andrew Diehl, Reg. No. P40,992; Thomas A. Hassing, Reg. No. 36,159; Edwin A. Sloane, Reg. No. 34,728; and Judith A. Szepesi, Reg. No. 39,393; my patent agents, with offices located at 12400 Wilshire Boulevard, 7th Floor, Los Angeles, California 90025, telephone (310) 207-3800, with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of First/Sole Inventor Richard Joseph Oliver

Inventor's Signature Richard Joseph Oliver Date 9/23/97

Residence Laguna Beach, CA Citizenship USA  
(City, State) (Country)

Post Office Address 21629 Ocean Vista Dr.  
Laguna Beach, CA 92677


Full Name of Second/Joint Inventor Roger Mather Duvall

Inventor's Signature Roger Mather Duvall Date 9/23/97


Residence Garden Grove, CA Citizenship USA  
(City, State) (Country)

Post Office Address 11442 Gill Drive  
Garden Grove, CA 92841

254350-00000000




**Fig. 1**  
(Prior Art)




**Fig. 2**

204260-66630



**Fig. 3**



**Fig. 4**